



Introducing a new range of Hisense airconditioners

Hisense Heat Pump Range

2.5kw, 3.5kw, 5.0kw, 7.1kw, 9.0kw



- **Quiet Mode**- our optimised air tunnel design keeps noise levels to a minimum without losing power or affecting performance.
- **Dual Functionality**- easily cools spaces in summer and warms them in winter.
- **Eco Mode**- when the heat of summer hits, eco mode offers energy saving performance to help you save on bills and energy.
- **Silver Ion Filter**- enjoy the benefits of a silver ion filter technology for cleaner air, free from bacteria and impurities.
- **I Feel Mode**- sit back and relax while i feel mode automatically sets temperature, direction and air flow, offering optimal performance, so you don't have to move a muscle.

fourways 

Hisense

Hisense Heat Pump Airconditioning (Inverter)

2.5kw, 3.5kw, 5.0kw, 7.1kw, 9.0kw



Quiet Mode



Eco Mode



Silver Iron Filter



I FEEL Mode

SPECIFICATIONS

MODEL		HSA25R	HSA35R	HSA50R	HSA71R	HSA90R
Indoor unit		HSA25R-I	HSA35R-I	HSA50R-I	HSA71R-I	HSA90R-I
Outdoor unit		HSA25R-O	HSA35R-O	HSA50R-O	HSA71R-O	HSA90R-O
Type		Reverse cycle	Reverse cycle	Reverse cycle	Reverse cycle	Reverse cycle
RATED VALUES						
Cooling Capacity	W	2500	3500	5000	7100	9000
Heating Capacity	W	3200	4000	6400	8000	9200
Rated Input-Cooling	W	510	805	1230	1975	2690
Rated Input-Heating	W	660	920	1630	2250	2630
Moisture Removal	Litre/Hour	0.9	1.2	2	2.5	3
Air Circulation	m ³ /h	620	620	1000	1200	1200
EER		4.90	4.35	4.07	3.59	3.35
COP		4.85	4.35	3.93	3.56	3.5
AEER		4.76	4.26	4.01	3.51	3.32
ACOP		4.76	4.26	3.88	3.51	3.5
Energy star rating for cooling		5	4	4	2.5	3
Energy star rating for heating		5	4	3.5	2.5	3
Refrigerant Type		R32	R32	R32	R32	R32
NOISE						
Indoor unit (fan mode high)	dB (A)	39	41	46	47	47
Indoor unit (fan mode silent)	dB (A)	25	25	32	32	35
Outdoor unit	dB (A)	59.5	61.5	63	66	69
POWER SUPPLY						
Voltage, Frequency, Phase		220-240V/50Hz-1Ph	220-240V/50Hz-1Ph	220-240V/50Hz-1Ph	220-240V/50Hz-1Ph	220-240V/50Hz-1Ph
Rated current cooling	A	2.3	3.6	5.5	8.8	12.1
Rated current heating	A	2.9	4.1	7.3	10.0	11.9
Maximum input power [c / h]	W	850/950	1200/1300		2800/2800	
Maximum input current	A	5.1/5.8	7.3/7.9		16/16	
SYSTEM						
Compressor type		Rotary	Rotary	Rotary/ Inverter	Rotary	Rotary/ Inverter
Expansion Device		Capillary	Capillary	Electronic Expansion Valve	Capillary	Electronic Expansion Valve
Evaporator		Copper tube and Aluminum Fin	Copper tube and Aluminum Fin	Copper tube and Aluminium Fin	Copper tube and Aluminium Fin	Copper tube and Aluminium Fin
Condenser		Copper tube and Aluminum Fin	Copper tube and Aluminum Fin	Copper tube and Aluminium Fin	Copper tube and Aluminium Fin	Copper tube and Aluminium Fin
PIPING						
Liquid pipe	inch	1/4	1/4	1/4	3/8	3/8
Gas pipe	inch	3/8	3/8	1/2	5/8	5/8
Maximum piping length/ height	m	20/10	25/10	30 / 20	30/20	40 / 20
FEATURES						
Transparent temperature display		Yes	Yes	Yes	Yes	Yes
LCD Wireless Remote Controller		Yes	Yes	Yes	Yes	Yes
Washable PP Filter		Yes	Yes	Yes	Yes	Yes
Silver Ion filter		Yes	Yes	Yes	Yes	Yes
24 Hours Timer		Yes	Yes	Yes	Yes	Yes
5 Speed and Auto mode for indoor fan control		Yes	Yes	Yes	Yes	Yes
Omnidirectional Air Flow		Yes	Yes	Yes	Yes	Yes
Dimmer		Yes	Yes	Yes	Yes	Yes
Sleep Operation		Yes	Yes	Yes	Yes	Yes
Smart Mode		Yes	Yes	Yes	Yes	Yes
Super Function		Yes	Yes	Yes	Yes	Yes
Demand Response		No	No	Yes	Yes	Yes
Auto Restart		Yes	Yes	Yes	Yes	Yes
Vertical Auto Swing Louver		Yes	Yes	Yes	Yes	Yes
Horizontal Auto Swing Louver		Yes	Yes	Yes	Yes	Yes
DIMENSIONS						
Net dimensions indoor unit	[WxHxD] mm	815×270×212	815×270×212	1085×315×235	1085×315×235	1280×346×257
Net dimensions outdoor unit	[WxHxD] mm	780×540×260	810×585×280	860×667×310	860×667×310	885×795×366
Net weight indoor unit	kg	8.5	8.5	13	13	18.5
Net weight outdoor unit	kg	30	33	40	51	61
Packing dimensions indoor unit	[WxHxD] mm	870×335×265	870×335×265	1170×390×315	1170×390×315	1385×435×325
Packing dimensions outdoor unit	[WxHxD] mm	910×600×360	940×630×385	995×720×420	995×720×420	1050×890×500
Gross weight outdoor unit	kg	11	11	16	16	22
Gross weight indoor unit	kg	33	36	43	54	65

Distributed & supported nationwide by Fourways Airconditioning



Contact Us

+08 6270 6366

sales@fourwaysaircon.com.au

leo@fourwaysaircon.com.au

1/15 Trade Road, Malaga, Perth, Western Australia, Australia, 6090

